



Document Cover Sheet

Thank you for downloading this document from the UXO Document Library hosted by UXOInfo.com - the largest source of UXO News and Information.

Please keep in mind that we did not create nor do we hold any copyrights to this document. We make the document available for reference purposes only. Please consult with the issuing agency or organization regarding the proper use of the document.

We accept document, report, and image donations for the UXO Library. Donations can be emailed to information@uxoinfo.com

Authority NNN 745 027
 By MS NARA Date 10-2-06

WAR DEPARTMENT
 AIR TECHNICAL SERVICE COMMAND
 MATERIAL DIVISION, AIR CORPS

OFFICE OF THE CHEMICAL WARFARE SERVICE LIAISON OFFICER

AIRMAIL!

CWWF 471.6/378-Secret

SECRETWLB:eb:TSXCW
WRIGHT FIELD, DAYTON, OHIO

19 June 1945.

Subject: 250 Kg. German Bomb Installation in AAF Planes.

SECRET

AUTH: Chief, C.W.S.
 Initials: WLB
 Date: 19 June 45

To: Chief, Technical Division, Office, Chief,
 Chemical Warfare Service, Army Service
 Forces, Washington, D. C.

1. This office, in conjunction with the Armament Laboratory, Engineering Division, has made a study on ways and means of using the subject munition in future operations. Since the bomb approximates the 500-lb. G.P. bomb in size, the goal was established as equivalent loading at 500-lb. stations. Further conditions imposed were: a. Fuze, AN-M-103, located in the nose, and, b. Field modifications minimum in number.

2. Since an adapter for the M-103 is required, it was felt that discarding the nose cover was an advantage, as it was used for carrying purposes primarily. This results in a desired reduction in length. The burster tube could be shortened but would be difficult to do in the field. The M-103 is recommended to be attached by an adapter - see Sketch A. Fairing for the nose is included with the adapter. Overall length of bomb with M-103 fuze is 64-1/4 inches.

3. The method of suspension had a number of variables: a. 14-inch spacing required; b. box-type fins require that the lugs be in line with one fin; c. if fuze well is used, no obstruction to be present; d. field modification required. These requirements can be met by the use of a curved plate with lugs spaced 14-inches and attached by standard metal band strapping available in the field. See Sketch B and photo. Rotation or longitudinal variations can be accomplished. For fore and aft movement, the banding was considered sufficient. Adopting these changes as suitable, space checks were started.

4. To obtain maximum loading in B-17, B-24, B-25, B-26, and all pursuit planes, a location of the front lug at 50 inches forward of tail or 8-3/4 inches forward of C.G. (center line of German suspension lug), is required.

5. This same spacing of 8-3/4 inches forward of C.G. is suitable for the rear bomb bays of the B-29 and B-32. To carry on the front rails of B-29 and B-32, a location of 4 inches forward of C.G. was found necessary. This spacing is also best for the A-26. (Due to special equipment location in the A-26 only, four bombs may be carried, or a reduction of two from the standard).

SECRET

PLEASE ADDRESS ALL COMMUNICATIONS TO "C. W. S. LIAISON OFFICER, MATERIAL DIVISION, WRIGHT FIELD, DAYTON OHIO".

int 70022

SECRET

6. Sketch B and photo show the design and application of the recommended suspension bar. Calculations indicate that four straps .020 x 3/4 inches are required to carry this bomb under a 11 g load.

7. The use of the T-51 fuze is not suitable to produce maximum 500-lb. loadings. Use of T-51 can be accomplished with the suspension bar located with C.G. midway between lugs. This will give maximum loading in B-17, B-24, B-25, B-26, all pursuits, A-26 (four only), and reduced load (24 per bomb bay reduced from maximum 40) in B-29 and B-32.

8. The use of the German fuze was not investigated thoroughly, as its operation details were not known. If electric current is required, it should not be too difficult to provide for in our aircraft.

9. It is suggested that consideration be given to a new fuze designed especially for this bomb and located in the side fuze well. Height of the fuze, if protruding from the bomb, will require a review of these results.

10. In summation, the following is suggested for use of subject munition:

- a. replace nose fairing and vertical suspension casting,
- b. install by clips or set screw M-103 fuze adapter and nose fairing,
- c. install by use of four straps a suspension plate with 1 1/4-inch lug spacing. Two locations are required as per paragraphs 4 and 5 above.

Willis L. Banks
WILLIS L. BANKS,
Major, C. W. S.,
Asst. C.W.S. Liaison Officer.

up
3 Incls.

Incl. 1 - Sketch A. } *1 cy w/d 8 sent to Edgewood 6/23 by ltr.*
Incl. 2 - Sketch B.
Incl. 3 - Photo.

cc: Chief, Tech. Command,
Edgewood Arsenal.
Air Chemical Officer,
Washington.
Maj. Carr, Tech. Div.,
Edgewood Arsenal.

*Incls. with memo
by J. F.*

SECRET